

M12 adaptor on rear of MSUD valve form A 18mm Replaced Art.-No. 13857

Form A (18 mm) ? M12, connector at the rear
without components
3-pole

Image

Vicarious picture

Approvals**Form**

41381

Technical Data

Operating voltage	125 V AC/DC
Operating current per contact (40 °C)	max. 4 A
Configuration	3 contacts + PE opposite plug contact
Switch off spike	<= 55 V
Current consumption	max. 15 mA
Protection	IP65 and IP67 when plugged and screwed down (EN 60529)
Temperature range	-25...+85 °C
Dimensions H x W x D	48 x 27 x 25 mm

Commercial data

Net weight	28
Net weight	28
Weight unit	gram
Basic unit	pc.
Customs tariff number	85366990
Unit (piece)	1
Limited value	1

Comments

Plastic housings with good resistance against chemicals and oils.
The resistance to aggressive media should be individually tested for your application. Further details on request.

All data on this data sheet was compiled carefully.
Liability regarding correctness, completeness, and actuality is limited to gross negligence. Created: 06/12

Representante oficial de:



[Argentina – Uruguay – Paraguay – Bolivia – Colombia – y Perú.]



Calle 49 N° 5764 - Villa Ballester (B1653AOX) - Prov. de Buenos Aires - ARGENTINA
Tel: (+54 11) 4768-4242 / Fax: (+54 11) 4849-1212
Mail: ventas@nakase.com.ar / Web: www.nakase.com.ar

