

Control units

Single-axis BASIC ANALOG



Control units

Single-axis ■ BASIC ANALOG

This control component allows you to enjoy the many benefits of digital drive technology on controls with the conventional ± 10 V analog interface. In addition, it gives you the added option of expanding your control equipment at any time to include other communication interfaces by exchanging the control component while retaining the control cabinet setup. The default speed is set via the analog input. Signals, such as “Control enable” or “Drive stop”, are exchanged by the control system and control unit via digital inputs and outputs. The encoder emulation inside the drive systematizes the actual positions for the control system. There is a choice between the straight-forward incremental encoder signal or SSI format. The correct interface for connecting the IndraDyn motors or other standardized encoders, such as Hiperface®, is already integrated.

Technical data

IndraDrive control units		
Master communication		
Analog interface		●
Configurations		
Option 1	Encoder interface	●
Safety option		●
Encoder interfaces		
IndraDyn motors MSK, MKE, MAD and MAF, Hiperface®, 1 Vpp and 5 V TTL		●
Safety options compliant with EN 13849-1 und EN 62061		
Safe Torque Off (Cat. 3 PL e/SIL 3)		
Expansions		
Encoder emulation		●
Operation panel		
Standard		●
Cycle times		
Current control	[μ s]	125
Velocity control	[μ s]	250
Position control	[μ s]	500
PWM frequency		
4 kHz		●
Inputs/outputs		
Digital inputs		5

Control units

Single-axis ■ BASIC ANALOG

Digital inputs/outputs (user-defined settings)		4
Analog inputs		2
Relay outputs		1
Interfaces		
RS232		●
Control voltage data		
Control Voltage		24 VDC
Power consumption without options	[W]	8

- Basic configuration
- Option

Representante oficial de:

Rexroth
Bosch Group

[Argentina]



Calle 49 N° 5764 - Villa Ballester (B1653AOX) - Prov. de Buenos Aires - ARGENTINA
Tel: (+54 11) 4768-4242 / Fax: (+54 11) 4849-1212
Mail: ventas@nakase.com.ar / Web: www.nakase.com.ar

