

MSUD double valve form B 10mm with cable PVC-JZ 4x0,75 yellow 1,5m

Form B (10 mm)
LED and suppression
Connection cable L = 100 mm

Image

Vicarious picture

Approvals**Form**

58201

Technical Data

Operating voltage	24 V AC/DC
Operating current per contact (40 °C)	max. 4 A
Switch off spike	<= 55 V
Switch off delay time	<= 20 ms
LED display	(yellow)
Current consumption	approx. 12 mA
Housing	Plastic, black (gray on request)
Temperature range	-25...+85 °C, depending on cable quality

Cable

No./diameter of wires	4 x 0.75 mm ²
Wire isolation	PVC (bk, num, gnye)
C-track properties	Max. Externe Vorsicherung 20 A (T) in der Gebäudeinstallation
Jacket	PVC
Outer diameter	approx. 6.2 mm
Bend radius (mobile)	10 x outer diameter
Temperature range (fixed)	-30...+70 °C
Temperature range (mobile)	-5...+70 °C

All data on this data sheet was compiled carefully.

Liability regarding correctness, completeness, and actuality is limited to gross negligence. Created: 06/12

Commercial data

Net weight	168
Net weight	168
Weight unit	gram
Basic unit	pc.
Customs tariff number	85444290
Unit (piece)	1
Limited value	1

Comments

Further cable lengths on request.
Plastic housings with good resistance against chemicals and oils.
The resistance to aggressive media should be individually tested for your application. Further details on request.

Contact layout

