

SVS valve form BI 11mm field-wireable Replaced Art.-No. 3129722

Form BI (11 mm)
110 V AC/DC with LED and VDR
PG 9

Image

Vicarious picture

Approvals**Form**

29901

Technical Data

Operating voltage	110 V AC/DC
LED display	(yellow)
Current consumption	approx. 12 mA
Suppression	Varistor
Switch off spike	<= 250 V
Switch off delay time	<= 10 ms
Hold-on	max. 100 W(VA)
Compression gland	PG 9
Clamping range (cable diameter)	6...8 mm
Terminals	4 mm ² single core, with ferrule end 1.5 mm ²
Plug color	Black housing, transparent flip top
Protection	IP65 when plugged and screwed down (EN 60529), with gland
Temperature range	-20...+60 °C

Commercial data

Net weight	30
Net weight	30
Weight unit	gram
Basic unit	pc.
Customs tariff number	85369010
Unit (piece)	1
Limited value	1

All data on this data sheet was compiled carefully.


Liability regarding correctness, completeness, and actuality is limited to gross negligence. Created: 06/12

Comments


Plastic housings with good resistance against chemicals and oils.

The resistance to aggressive media should be individually tested for your application. Further details on request.

Contact layout



Circuit diagram



Representante oficial de:



[Argentina – Uruguay – Paraguay – Bolivia – Colombia – y Perú.]



Calle 49 N° 5764 - Villa Ballester (B1653AOX) - Prov. de Buenos Aires - ARGENTINA
Tel: (+54 11) 4768-4242 / Fax: (+54 11) 4849-1212
Mail: ventas@nakase.com.ar / Web: www.nakase.com.ar

